IP CABLING TRANSMISSION – POE Repeater

ITEM NO.: IP04X High Power POE Repeater

IP04X is a High Power POE repeater to extend power and data an additional 100meters. Multiple units are allowed for longer distance, eliminating the need for additional switches, hubs and expensive fiber installations. It compliant with standard POE IEEE802.3af and IEEE802.at



IP04X High Power POE Repeater

- Extend of both power and data beyond 100 meters.
- Allow to use multiple repeaters for longer range.
- No external power required.
- Compatible IEEE802.af and IEEE 802.3at POE standard.
- Auto-sensing for detecting PoE or non-PoE devices.
- Support 10/100/1000 BASE-T transmission rate.
- Built in LED status indication.
- Perfect for long range outdoor POE camera use.
- Plug and play for easy installation.

Installation View:


IP04X itself provide data and power 120 meters, the power will drop as below by multiple POE repeaters and long cable length application:


Max Device Power	1 st IP04X Max.	2 nd IP04X Max.	3rd IP04X Max.
Range with PoE switch	18.84W at 240M	12.18W at 360M	5.52W at 480M



1

Panel View:





Linking Cable:

Use CAT.5e UTP/STP or CAT.6 UTP cable

LED Indication:

LED (Green)	ON	PSE send power	
	OFF	PSE non-power	
RJ45 (Yellow)	ON	1000 Mbps link	
	OFF	1000 Mbps unlink	
	FLASH	Activity	
RJ45 (Green)	ON	10/100 Mbps link	
	OFF	10/100 Mbps unlink	
	FLASH	Activity	

Option Model:

IP06I: High Power POE injector IEEE 802.3at POE standard.
IP06H: 5 Port High Power POE Switch IEEE 802.3at POE standard.

Specification:

Specification.			
ITEM NO.	IP04X		
Power & Data Input/Output	RJ45		
Data Link	Pin 1/2 · 3/6 · 4/5 · 7/8		
Power Link	Pin 1/2 (+) [,] 3/6 (-) End-Span		
Transmission Range	3 pieces repeater up to 480 Meters		
LED Indication	Power: Green, Data link: Yellow/Green		
POE	IEEE 802.3af and IEEE 802.3at Standard		
Power Consumption	Non-load 1.62W (30mA) , 1.89W (35mA) @ 10Mbps , 2.16W (40mA)		
	@ 100/1000Mbps		
Temperature	Operation: 0 to 55°C, Storage: -20 TO 85°C, Humidity: up		
,	to 95%		
Dimensions mm	67×110×27 mm		
Weight g	180g		



Rev.A